



TECHNICAL SPECIFICATIONS	
SASH WIDTH	32 mm
SASH LENGTH	75 mm
FRAME LENGTH	44 mm
GLASS THICKNESS	20 - 22 mm
MAX. SASH CARRYING CAPACITY	120 kg
INSULATION BRIDGE	20 mm
THE MIDDLE SASH WIDTH	34 - 78,5 mm

APPLICATION FEATURES	
SPECIAL STEEL RAIL	✓
FLY SCREEN	✓
MULTI LOCK APPLICATION	✓
EASE OF USE AND FUNCTIONALITY	✓
MINIMAL MIDDLE SASH	✓
45° AND 90° SASH JOINT	✓
3 TRACK FRAME	✓
MONO RAIL FRAME	✓

- **Minimal Architectural Solution:** Provides a clean, modern appearance with a 50% reduced center mullion for enhanced transparency.
- **Project-Friendly Customization**
Tailor-made design options available to suit various project requirements.
- **High-Strength Locking System** Specially designed multi-point locking mechanism for enhanced security.
- **Polyamide Hollow Center Detail**
Polyamide-profiled hollow center for improved structural performance.

MINIMAL
MIDDLE SASH DETAIL

Clean Lines, Strong Performance
Opens Up Spaces with Confidence.



EASE OF
INSTALLATION



FLY SCREEN
DESIGN