

34 mm middle sash profile at 90° sash joints allows more light to enter your home.

Special fly screen rail frame and useful fly screen sash in 90° and 45° sash combinations

TECHNICAL SPECIFICATIONS

SASH WIDTH	32 mm
SASH LENGTH	75 mm
FRAME LENGTH	44 mm
GLASS THICKNESS	30 - 32 mm
MAX. SASH CARRYING CAPACITY	120 kg
INSULATION BRIDGE	21 mm
THE MIDDLE SASH WIDTH	34 - 78,5 mm

APPLICATION FEATURES

WATER, AIR INSULATION	✓
ENERGY SAVINGS	✓
SPECIAL STEEL RAIL	✓
FLY SCREEN	✓
MULTI LOCK APPLICATION	✓
EASE OF USE AND FUNCTIONALITY	✓
MINIMAL MIDDLE SASH	✓
45° AND 90° SASH JOINT	✓
3 TRACK FRAME	✓
MONO RAIL FRAME	✓

Clean Lines, Strong Performance
Opens Up Spaces with Confidence.

- **Minimal Architectural Solution:** Provides a clean, modern appearance with a 50% reduced center mullion for enhanced transparency.
- **High-Security Locking:** Equipped with a specially designed high-strength multi-point locking system for improved safety.
- **Thermal Efficiency:** Features a polyamide-profiled hollow center detail to support thermal insulation.
- **Ease of Use:** Designed for simplified production and installation, reducing labor time and complexity.



SOUND
PERFORMANCE



WATER
ISOLATION



EASE OF
INSTALLATION



FLY SCREEN
DESIGN

PIATTA HANDLE