

TECHNICAL SPECIFICATIONS	
SIDE FRAME PROFILE	85 / 133 mm
BOTTOM FRAME PROFILE	26 / 133 mm
MOTOR BOX PROFILE	141.5 / 133 mm
ADAPTER SASH PROFILE	61.55 / 103.78 mm
SASH PROFILE	29.5 / 35 mm
INTERLOCK SASH PROFILE	43.35 / 35 mm

APPLICATION FEATURES	
EASY CLEANING SYSTEM	✓
MAXIMUM INSULATION	✓
CONCEALED RAIL DESIGN	✓
EASY SERVICE & INSTALLATION	✓
SAFE OPERATION DETAIL	✓
WIDE SYSTEM VARIATIONS	✓

Experience Open-Space Comfort
Live All Four Seasons

- **Motorized Guillotine Technology:**
Provides remote-controlled vertical movement with a chain-driven silent motor system.
- **Panoramic Usage Advantage:**
Offers maximum openness without interrupting the view, creating spacious living areas for terraces and balconies.
- **Fixed Glass Railing Function:**
When fully opened, the system can safely function as a fixed glass railing.
- **Insulated Compatible Structure:**
Applicable with 4-16-4 and 6-12-6 tempered insulated glass combinations.
- **Panel Options:**
Offers 2-panel or 3-panel production alternatives according to the application area.

